

MLS-801 Microwave Landing System Ramp Test Set

The MLS-801 ramp test set provides Microwave Landing System angle receiver go/no-go verification testing



- **Rugged construction, meets MIL-T-28800D, Type 2, Class 2, Style A requirements**
- **Automatic Test Sequence mode to allow one person operation**
- **Control Motion Deflection Position to test auto-pilot coupling**
- **Complete simulation of the MLS transmission cycle, including all angular information as well as data words**
- **Built-In-Test (BIT) for confidence testing and fault isolation of the test set**
- **Manual deflection controls for both Azimuth and Elevation**
- **Two power output levels for short and long range testing requirements**
- **Internal battery allowing 2 hours (approx.) of operation before recharge. Automatic power shutdown after approximately 15 minutes of non-use**

IFR is a leader in the design, manufacture and marketing of Avionics test systems.

The MLS-801 ramp test set provides go/no-go verification of the Microwave Landing System angle receiver installed in an aircraft. The test set generates a single channel signal that includes all necessary AM and DPSK modulation for testing of the azimuth, elevation, back azimuth and clearance functions as well as all basic data words in their standard test conditions.

Controls on the IFR MLS-801 provide for angle offset, deviation and slewing in order to allow the operator to exercise the Glideslope and Localizer deviation, to observe control surface motion and to test offset approach angles.

Other Features

- Dynamic Slew capability at 0.05, 0.1, 0.5 and 1.0 degrees/second.
- Left and Right Clearance pulse simulation.
- Azimuth, High Rate Azimuth and Back Azimuth offset approach simulation of up to 40 degrees.
- Elevation approach angle simulation from 1 to 10 degrees.
- Fixed transmission frequency, set to the FAA specified channel (500).
- Auxiliary RF, Video and Sync Pulse outputs for use in limited bench testing.

Specification

RF FREQUENCY

MLS Channel 500, 5031 MHz \pm 10 kHz

RF LEVEL

HIGH Range

-69.5 dBW/m² @ 30 ft.; Range approximately 300 ft.

LOW Range

-89.5 dBW/m² @ 30 ft.; Range approximately 30 ft.

MODULATION

AM and DPSK signals that conform to FAA 14

CFR Part 17 requirements. Phase accuracy is 180 \pm 10 degrees

BEAM LEVEL

Fixed at 6 dB above the preamble; Accuracy \pm 2 dB

BEAM WIDTH

AZ, BAZ and EL:	1.0°
HiAZ:	3.0°

Accuracy

±10% (measured at the -3 dB point)

ANGLE OFFSET

Azimuth:	±40° in 10° steps
Elevation:	+1 to +10° in 1° steps

Accuracy

±0.1°

CLEARANCE PULSE

Levels

CLR L:	+6 dB LEFT PULSE and -4 dB RIGHT PULSE
CLR R:	-4 dB LEFT PULSE and +6 dB RIGHT PULSE

Width

1/2 Beam plus Clearance Pulse at -3 dB point (75µs)

Position

Pulse fixed at ±12.5° (Pulses fixed at -12.5° left and +12.5° right)

DEFLECTION

Center

0% Full Scale Deflection (FSD)

Accuracy: ±0.1°

Full

100% FSD (left and right 3.2 degrees Azimuth)

Standard

52% FSD

Control Motion

7% FSD

SLEW

Slew Rate

0.0, 0.05, 0.1, 0.5 and 1.0° per second

Accuracy

± 0.05° per second

General

Operating Temperature

-25° C to +55° C

Storage Temperature

-40° C to +60° C

Battery

Two hour battery operation with 15 minute time-out following the absence of switch operation

AC

Selectable VAC operation used to recharge the battery and operate the test set; 103.5 to 129 VAC or 207 to 253 VAC, 47.5 to 420 Hz, 50 W

Dimensions

343 mm wide, 368 mm deep, 209 mm high
13.5 in. wide, 14.5 in. deep, 8.25 in. high

Weight

13.5 kg (30 lbs.) approximately

Versions and Accessories

When ordering please quote the full ordering number information.

Ordering Numbers

Versions

801	MLS-801 Microwave Landing System Ramp Test
801-C	MLS-801 Microwave Landing System Ramp Test with Certificate of Calibration

All IFR Avionics products delivered with Factory Certificate of Calibration

IFR - "Working together to create solutions for the world of communications."

IFR is a world leader in developing leading edge test and measurement equipment. The priority at IFR is to understand your communications test needs and respond to them. IFR has the flexibility and expertise to create just the right test solution for you. We understand that just as you are the expert in designing wireless products, we are expert in wireless test.

Combining the quality of our test products with their reliability, excellent price/performance ratio and minimal requirements for maintenance, every IFR test system represents an outstanding lifetime value.

IFR - "Working together with our customers to be flexible and innovative in providing effective test solutions for the rapid design, manufacture and maintenance of communications systems."

The added value IFR includes with each and every test set we sell will make you more productive. We offer a two-year standard warranty on all products and we will continue to support your product for five years beyond its final production. Our outstanding Customer Service Department offers calibration, out-of warranty repairs and consulting. Our Sales and Training Departments offer clear and concise product information with realistic performance specifications, technology training and application training. Our experienced engineers will help you develop application software and through continuous improvement programs, upgrades are always available.

IFR will continue to build upon our technology resources with an aggressive commitment that will enable you to excel in some of the world's most dynamic, high growth markets.

CHINA

Tel: [+86] (10) 6467 2823

Fax: [+86] (10) 6467 2821

FRANCE

Tel: [+33] 1 60 79 96 00

Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] (8131) 29260

Fax: [+49] (8131) 2926130

HONG KONG

Tel: [+852] 2832 7988

Fax: [+852] 2834 5364

LATIN AMERICA

Tel: [+1] (972) 899 5150

Fax: [+1] (972) 899 5154

SCANDINAVIA

Tel: [+45] 9614 0045

Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34

Fax: [+34] (91) 640 06 40

UNITED KINGDOM

Chandlers Ford

Tel: [+44] (0) 2380 273722

Fax: [+44] (0) 2380 254015

Stevenage

Tel: [+44] (0) 1438 742200

Fax: [+44] (0) 1438 727601

USA

Tel: [+1] (316) 522 4981

Toll Free: [+1] (800) 835 2352 (US only)

Fax: [+1] (316) 522 1360

email **info@ifrsys.com**

web **www.ifrsys.com**

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company IFR Systems, Inc. © IFR 2002.

Part No. 46891/037

Issue 1

03/2002

